


FEATURES	
Technology	Basic
Energy Metering	No
Metering per Input Line	No
Metering per Output Receptacle	No
Remote Outlet Switching	No
Ethernet Port	No
Networking Protocols	No
PDU Cascading	No
Power Share	No
Display	No
Residual Current Monitoring	No
USB Ports	No
Environmental Sensors	No
INPUT	
Plug	IEC 60309 1P+N+E 6h 32A 250V SINGLE PHASE
Lead Length	3 meter
Cable Type	H07RN-F3G4.0 mm ²
Max. Input Load	32A
Rated Input Voltage	190-250V Single phase
Frequency	50-60Hz
Power Capacity	7360W
OUTPUT	
Rated Output Voltage	190-250V Single phase
Output Types	12 IEX (C13/C19) combo (Max rate 16A) EN61984+UL498 certified
Overload Protection	(2) 1 Pole Carling 16A L31-X1-00-445-H62-D3
CHASSIS	
Dimensions (W x D x H)	483 x 44.4 x 110 mm
Color	RAL 9004 black powder coat
Mounting Options	(2) Mounting Bracket
Required Torque for Mounting Screws	≥2.54N·m (25.9kgf-cm or 22.4 in-lbs)
OPERATING ENVIRONMENT	
Temperature Range	0° to 60° C (30° to 140° F)
Humidity	0 - 95 %
Elevation	0 - 4000 Meters
CONFORMANCE	
IEC 62368-1 (Third Edition)	
   	




IEC is C13/C19 combination outlet P-LOCK and standard plug compatible

IEC





100%





C13 locking, compatible with standard C14 plug, C14 P-Lock and C14 V-Lock plug


C13 Lock Part



Mounting Bracket




483




110

44.4



430



M6x12 Screw+ring

Chassis Color	Code
Black	Standard color
White	W
Red	R
Blue	A
Green	G
Orange	O
Grey	GY
Yellow	Y

DRAWING TYPE  (NO PERMISSION.NO CHANGING)		WZ-LZ-B13212IEX	
unit=mm		Housing	Aluminium
TECHNICAL STANDARD IT11; NO RUSTNESS NO FLAW ON THE SURFACE			Black Powder coating
			RAL9004
FILLET	R0.5	Zpas	
ANGLE	±0.5°		
FIRST ANGLE 			
		DATE 11-07-2022	

Basic Series

OUTPUT

OPERATING TEMPERATURE

(12) IECX (C13/C19) combo Black (Max rate 16A)

0° to 60°C

Revisions

Rev

Description

Date

INPUT

BRANCH CIRCUITS

MOUNTING ACCESORIES

230VAC 32A 50HZ
IEC60309 32A 1P+N+E plug
3m H07RN-F3G4.0mm² Power lead

(2) 1 Pole Carling 16A
L31-X1-00-445-H62-D3

(2) Mounting Bracket

- Low cost locking solution at both ends
- Different colors available
- Patented IEX locking system
- Locking sleeve for C13 and C19 plugs
- VDE, UL approved

IEX PATENTED LOCKING SOCKET - POWER CORD SOLUTION



C14 - C13 Sleeve

H05VV-F3G1 mm²

Color	0,5M	1M	2M
Black	✓	✓	✓
Red	✓	✓	✓
Blue	✓	✓	✓



C14PLOCK - C13 Sleeve

H05VV-F3G1 mm²

Color	0,5M	1M	2M
Black	✓	✓	✓
Red	✓	✓	✓
Blue	✓	✓	✓



C20PLOCK - C19 Sleeve

H05VV-F3G1,5 mm²

Color	1M	2M
Black	✓	✓
Red	✓	✓
Blue	✓	✓



C20PLOCK - C13 Sleeve

H05VV-F3G1 mm²

Color	1M	2M
Black	✓	✓
Red	✓	✓
Blue	✓	✓

