

FEATURES

Technology	Basic
Energy Metering	No
Metering per Input Line	No
Metering per Output Receptacle	No
Remote Outlet Switching	No
Ethernet Port	No
Networking Protocols	No
PDU Cascading	No
Power Share	No
Display	No
Residual Current Monitoring	No
USB Ports	No
Environmental Sensors	No

INPUT

Plug	IEC60309 3P+N+E 6h 32A 380-415V
Lead Length	3 meter
Cable Type	H07RN-F5G4.0 mm ²
Max. Input Load	32A
Rated Input Voltage	380-415V three phase
Frequency	50-60Hz
Power Capacity	22.1kW

OUTPUT

Rated Output Voltage	190-250V Single phase
Output Types	39 IEX (C13/C19) combo (Max rate 16A) EN61984 + 6 CamdenBOSS Green LED
Overload Protection	(6) 1 Pole Carling 16A L Series L31-B0-24-616-H12-D3

CHASSIS

Dimensions (W x D x H)	1688.2 x 44.4 x 60 mm
Color	RAL 9004 black powder coat
Mounting Options	(2) New 45 Bracket + (2) Toolless Button + M5x8
Required Torque for Mounting Screws	≥2.54N·m (25.9kgf-cm or 22.4 in-lbs)

OPERATING ENVIRONMENT

Temperature Range	0° to 60° C (30° to 140° F)
Humidity	0 - 95 %
Elevation	0 - 4000 Meters



CONFORMANCE

IEC 62368-1 (Third Edition)




1 2 3 4 5 6 7 8

A



A

B



B

C




C



D

Packing content:

IEX Lock-VP



X39 (black,white,grey)

Chassis Color	Code
Black	Standard color
White	W
Red	R
Blue	A
Green	G
Orange	O
Grey	GY
Yellow	Y

Basic Series	OUTPUT (13) IEX (C13/C19) combo Black (Max rate 16A) (13) IEX (C13/C19) combo White (Max rate 16A) (13) IEX (C13/C19) combo Grey (Max rate 16A) (6) CamdenBOSS Green LED	OPERATING TEMPERATURE 0° to 60°C
INPUT 380-415VAC 32A 50HZ IEC60309 32A 3P+N+E Plug 3m H07RN-F5G4.0mm² Power Lead	BRANCH CIRCUITS (6) 1 Pole Carling 16A L Series L31-B0-24-616-H12-D3	MOUNTING ACCESORIES (2) New 45 Bracket (2) Toolless Button + M5x8

Revisions		
Rev	Description	Date

DRAWING TYPE (NO PERMISSION,NO CHANGING)	WZ-LZ-B33239IEXS/LED	
unit=mm	Housing	Aluminium
TECHNICAL STANDARD 1.IT11; 2.NO RUST 3.NO FLAW ON THE SURFACE		Black Powder Coating
FILLET R0.5		RAL9004
ANGLE ±0.5°	DATE 14-10-2022	
FIRST ANGLE 		

D

E

E

F

F

1 2 3 4 5 6 7 8

- Low cost locking solution at both ends
- Different colors available
- Patented IEX locking system
- Locking sleeve for C13 and C19 plugs
- VDE, UL approved

IEX PATENTED LOCKING SOCKET - POWER CORD SOLUTION



C14 - C13 Sleeve

H05VV-F3G1 mm²

Color	0,5M	1M	2M
Black	✓	✓	✓
Red	✓	✓	✓
Blue	✓	✓	✓



C14PLOCK - C13 Sleeve

H05VV-F3G1 mm²

Color	0,5M	1M	2M
Black	✓	✓	✓
Red	✓	✓	✓
Blue	✓	✓	✓



C20PLOCK - C19 Sleeve

H05VV-F3G1,5 mm²


Color	1M	2M
Black	✓	✓
Red	✓	✓
Blue	✓	✓



C20PLOCK - C13 Sleeve

H05VV-F3G1 mm²

Color	1M	2M
Black	✓	✓
Red	✓	✓
Blue	✓	✓



DRAWING TYPE		WZ-LZ-B33239IEXS/LED-wiring	
 (NO PERMISSION.NO CHANGING)			
unit=mm		Housing	
TECHNICAL STANDARD IT11; NO RUST NO FLAW ON THE SURFACE			
FILLET	R0.5		
ANGLE	±0.5°		
FIRST ANGLE			
			
		DATE 28-09-2023	