

SZB IT Data Communication Cabinets

Catalogue number: W-IT-XXX0X0-69AA-2-011

ZPAS

W-IT-428080-69AA-2-011

PRODUCT DESCRIPTION

Cabinet for ICT applications based on a bolted frame.
Static load capacity 1000 kg.

Functionality

- 71 mm wide cable openings in the top and bottom plates allow to put thought the power cords with three-phase plug.
- Ventilation perforation in the top plate.
- All openings in the top and bottom plates blanked with knock-out blanking plates.
- U-marking on the mounting profiles.
- Maximum opening angle for front door – 270°.
- Door opening direction can be changed.
- Possibility to put the cabinet directly on the floor (no protruding elements under the cabinet).
- Adaptation for bying the cabinets in the rows.

CONFIGURATION

- Bolted frame (bottom plate, top plate, four posts).
- Front glass door with metal sides and single-point lock with swing handle.
- Rear solid metal, shortened door with single-point lock without handle; 3U cable entry panel with a brush strip, mounted under the shortened door.
- Two solid metal side panels with single-point locks.
- Two pairs of 19" mounting profiles, type STANDARD.
- Earthing bar.
- Door and side panels earthing conductors (not shown in photos).
- Four levelling feet.

TECHNICAL DATA**Material**

Frame, side panels, rear door, mounting profiles, C-profiles – sheet steel.

Front door – sheet steel, clear mineral safety glass.

Outriggers – zamak casting.

Protection degree

IP 20 in accordance with EN 60529
(does not apply to brush cable entry).

Surface finishing

Frame, side panels, doors

– powder paint, light grey (RAL 7035).

Mounting profiles, C-profiles





– Al-Zn coated.

REFERENCE CHART

Usable height HU	Frame height H [mm]	Width W [mm]	Depth D [mm]	RAL colour	Weight [kg]	Catalogue number
24 U	1163	600	600	7035	62	W-IT-246060-69AA-2-011
			800	7035	70	W-IT-246080-69AA-2-011
		800	600	7035	70	W-IT-248060-69AA-2-011
			800	7035	80	W-IT-248080-69AA-2-011
42 U	1963	600	600	7035	90	W-IT-426060-69AA-2-011
			800	7035	100	W-IT-426080-69AA-2-011
		800	600	7035	100	W-IT-428060-69AA-2-011
			800	7035	116	W-IT-428080-69AA-2-011
45 U	2096	600	600	7035	94	W-IT-456060-69AA-2-011
		800	800	7035	125	W-IT-458080-69AA-2-011

SZB IT Data Communication Cabinets












Catalogue number: W-IT-XXX0X0-69AA-2-011

ZPASA-A section
(800 mm deep cabinet)C-C section
(800 mm deep cabinet)A-A section
(600 mm deep cabinet)C-C section
(600 mm deep cabinet)**DESIGN**

1. Frame's post
3. Frame's bottom plate
4. Frame's top plate
5. Adjustable feet
6. C-profile for 15 mm deep mounting profiles
7. Outrigger
8. 19" mounting profile, type STANDARD, 15 mm deep
9. Earthing bar
10. Knock-out blanking plate 380 x 380 mm
12. Knock-out blanking plate 380 x 71 mm

Note:

The cabinet in the drawing is shown without any panels or doors.

Widok z przodu
(szafa o szerokości 600 mm)Front view
(800 mm wide cabinet)Side view
(600 mm deep cabinet)Side view
(800 mm deep cabinet)B-B section
(600 mm deep cabinet)D-D section
(600 mm deep cabinet)B-B section
(800 mm deep cabinet)D-D section
(800 mm deep cabinet)

19" mounting profile
type STANDARD
15 mm deep