SZE2 System Cabinet, 2000 x 800 x 600 mm

Catalogue number: WZ-SZE2-2008-S10A-00-111-00-0-011



MULTIFUNCTIONALITY

- Designed for indoor applications.
- Cabinet includes: cabinet's frame, single-leaf front door with a lock that incl. double-bit insert (no handle), rear panel, mounting plate for the full height of the cabinet, blanking plates for cabinet's top plate, set of sliding gland plates for cabinet's bottom plate.
- Side panels are available as accessories, to be ordered separately.
- Design of the cabinet allows easy baying in rows.
- The frame includes holes for attaching a mounting bar system or mounting plate.
- The frame's top plate includes opening for cable entry or the installation of fan unit. This opening is covered by blanking plate.
- The frame's bottom plate includes opening for cable entry. This opening is covered by sliding gland plates.
- Easy change of the door opening direction (turning the door leaf and lock).
- Maximum door opening angle is 120°.



TECHNICAL DATA

Material

Sheet steel.

Protection degree

IP 54 for cabinet equipped with side panels (ordered separately);

IP 55 for cabinet equipped with side panels and sealing set for bottom plate (ordered separately).

Surface finishing

Cabinet's frame, doors, rear panel, blanking plate for top plate - powder painted in RAL 7035 (epoxide--polyester paint, applied for internal conditions). Mounting plate, door stiffening frames, sliding gland plates for bottom plate - zinc coated.

Maximum load capacity

1000 kg if equipment installed on the mounting plate, 1600 kg if equipment installed on a structure made of mounting bars fixed to the frame, 20 kg if equipment installed on door.

Dimensions

Height: 2000 mm Width: 800 mm Depth: 600 mm



SZE2 System Cabinet, 2000 x 800 x 600 mm

Catalogue number: WZ-SZE2-2008-S10A-00-111-00-0-011



