

SZB IT Data Communication Cabinet 47 U, 800 x 1200 mm

Catalogue number: WZ-IT-478012-65AA-2-011

ZPAS**PRODUCT DESCRIPTION**

Cabinet for ICT applications based on a bolted frame.
Static load capacity verified by external testing at 1500 kg.

Functionality

- 71 mm wide cable openings in the top and bottom plates allow to put thought the power cords with three-phase plug.
- Ventilation perforation in the top plate.
- All openings in the top and bottom plates blanked with knock-out blanking plates.
- U-marking on the mounting profiles.
- Maximum opening angle for front and rear door – 270°.
- Possibility to put the cabinet directly on the floor (no protruding elements under the cabinet).
- Adaptation for bying the cabinets in the rows and Data Box creation (cold/hot aisle).
- Three-point locking system for front doors.

CONFIGURATION

- Bolted frame (bottom plate, top plate, four posts).
- Front glass door with metal sides and lock with swing handle.
- Rear double-leaf perforated metal door (clearance 80%) with swing handle.
- Two pairs of 19" mounting profiles, type STANDARD.
- Solid metal side panels with single-point locks.
- Door and side panels earthing conductors (not shown in photos).
- Four levelling feet.

TECHNICAL DATA**Material**

Frame, side panels, perforated door, mounting profiles, C-profiles – sheet steel.

Door with glass – sheet steel, clear mineral safety glass.

Outriggers – zamak casting.

Protection degree



IP 20 in accordance with EN 60529.

Surface finishing

Frame, side panels, doors – powder paint, light grey (RAL 7035).
Mounting profiles, C-profiles – Al-Zn coated.

SZB IT Data Communication Cabinet 47 U, 800 x 1200 mm

Catalogue number: WZ-IT-478012-65AA-2-011

ZPAS**DESIGN**

1. Frame's post
2. Frame's middle post
3. Frame's bottom plate
4. Frame's top plate
5. Adjustable feet
6. C-profile for 15 mm deep mounting profiles
7. Outrigger
8. 19" mounting profile, type STANDARD, 15 mm deep
9. Earthing bar
10. Knock-out blanking plate 380 x 380 mm
11. Knock-out blanking plate 380 x 71 mm

Note:

The cabinet in the drawing are shown without any panels or doors.